

Flexi type unit

FLXS-B9/RXS-L3/RXS-L/FLXS-B



Home leave operation



Indoor unit silent operation



Vertical auto swing



Online controller via app



Multi model application

Flexible unit, ideal for rooms without false ceiling, can fit on either ceiling or wall

- › Can fit on either ceiling or lower wall; its low height enables the unit to fit beneath a window
- › Home leave operation maintains the indoor temperature at your specified comfort level during absence, thus saving energy

- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › Online controller: control your indoor from any location with an app, via your local network or internet

FLXS-B9/RXS-L3/RXS-L/FLXS-B + RXS-L



Indoor unit		FLXS	50B
Casing	Colour		Almond white
Dimensions	Unit	HeightxWidthxDepth	mm
			490x1,050x200
Sound power level	Cooling		dB
			60
Sound pressure level	Cooling	High/Low/Silent operation	dB
			47/39/36
	Heating	High/Low/Silent operation	dB
			46/35/33
Control systems	Infrared remote control		ARC433B67
Refrigerant	Type		R-410A
	GWP		-

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load


Efficiency data		FLXS + RXS	50B + 50L	
Cooling capacity	Min./Nom./Max.	kW	0.9/4.9/5.3	
Heating capacity	Min./Nom./Max.	kW	0.9/6.1/7.5	
Power input	Cooling	Min./Nom./Max.	kW	
			0.450/1.720/1.950	
	Heating	Min./Nom./Max.	kW	
			0.310/1.820/3.540	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A	
		Pdesign	kW	
		SEER	5.25	
	Heating (Average climate)	Annual energy consumption	kWh	326
		Energy label	A	
		Pdesign	kW	4.20
Nominal efficiency	SCOP/A		3.80	
	Annual energy consumption	kWh	1,546	
EER			2.85	
			3.35	
	Annual energy consumption	kWh	860	
	Energy label	Cooling/Heating	C/C	

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Outdoor unit		RXS	50L
Dimensions	Unit	HeightxWidthxDepth	mm
			735x825x300
Sound power level	Cooling		dB
			62
Sound pressure level	Heating		dB
			62
Operation range	Cooling	High/Low	dB
			48/44
	Heating	High/Low	dB
			48/45
Refrigerant	Cooling	Ambient	Min.-Max.
			°CDB
Power supply	Heating	Ambient	Min.-Max.
			°CWB
			-10~46
			-15~18
Refrigerant	Type/Charge/GWP	kg/TCO ₂ eq	R-410A/1.7/3.5/2,087.5
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-230-240

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-030 07/16



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.